

Integrated Sustainability Assessment and Optimization of Energy Systems

Claudia Sutardhio, Anke Weidlich, Tobias Naegler

Department of Sustainable System Engineering

University of Freiburg



INATECH InNOSys Project

Project Partners:



Deutsches Zentrum für Luft- und Raumfahrt German Aerospace Center Institute of Engineering Thermodynamics

GLIS

SPECIALISTS IN EMPIRICAL ECONOMIC RESEARCH

DEPARTMENT OF SUSTAINABLE

SYSTEMS ENGINEERING



Supported by:

Federal Ministry for Economic Affairs and Energy

on the basis of a decision by the German Bundestag INEC INSTITUTE FOR INDUSTRIAL ECOLOGY PFORZHEIM







Energy Days 2018 | INATECH



Energy scenarios studies for sustainable transformation (2050)



The main objective of InNOSys (Integrated Sustainability Assessment and Optimization of Energy Systems) project is to develop new generic modelling and assessment approaches for energy scenarios, as well as deriving optimized pathways of energy systems in Germany from a sustainability perspective.

Energy Days 2018 | INATECH

BURG

Fraunhofe

18 Dezember 201



INATECH Objectives

- To develop interdisciplinary, integrated methods for the sustainability assessment of transformation scenarios for (the German) energy systems
- To optimize expansion in the power generation capacity under consideration of ecological, economical and social sustainability aspects
- To identify and analyze the conflicting goals and trade-offs between different sustainability indicators
- To formulate conclusions for energy policy and society with respect to alternative courses of action





INATECH Sustainability Indicators

 Sustainability is a triad of ecology, economics and social acceptability [Eizenberg, 2017]

Ecological	Economical	Social/Ethical
 Change in forest area Land use GHG emissions CO2 emissions SO2 emissions NOx emissions Nuclear waste Fine dust emissions Acidification 	 Investment cost O&M Cost Import dependence LCOE 	 Job creation Social acceptance Local manufacturing share Competition to food production
		-



^H Multi-Criteria Decision Analysis (MCDA)

 Multi-criteria decision analysis (MCDA) is a formal, structured and transparent decision making methodology. It aims to assist groups or individual decision makers to explore their decisions in the case of complex situations with multiple criteria.





INATECH Multi-Attribute Decision Making (MADM)

- MADM: Multi-attribute utility functions
 - \rightarrow Aim: Make a choice among several alternatives
- General idea:





INATECH Case Study for Sustainability Assessment

			Scenar	io j								
	1	2	3	4	-							
	BAU	DivCoal	DivNuc	DivCoalRes	DivRes							
Criteria <i>i</i>		Performan	the x_{ij} of crit	teria <i>i</i> in scenario	j	Unit						1
1	13.9	13.1	13.7	13.6	14.4	billion €						
2	69.9	64.4	68.1	67.0	72.4	€/MWh	0.8 -		١	MCDA TOP	SIS	
3	1.63	1.36	1.53	1.20	1.13	point [-22]	0.0					
4	2822	1846	2447	1831	2424	PJ	- 7.0 rtion					
5	-1.85	-1.55	-1.85	-1.39	-1.36	point [-22]	- 6.0 Solt					
6	21.7	21.4	18.9	24.7	29.5	%	0.5 -			2		
7	0.75	0.42	0.53	0.81	1.08	point [-22]	ਸ਼ \$ 0.4 -					
8	3650	5690	5460	7360	8890	jobs	seuess					
9	167	226	144	206	143	Mt CO ₂	0.3 - CO					
10	0	22	0	18	0	kt SO ₂	- 2.0 ative					
11	19	48	16	42	16	kt NO _x	0.1 -					
12	0	0	149	0	0	t nuc. waste	0.0		1			
13	0	2150	0	1800	0	t fine dust		BAU	DivCoal E	DivNuc nergy Scena	DivCoalRes rios	DivR

- Case study for sustainability assessment in Tunisia
- Five energy scenarios and 13 sustainability criterias
- TOPSIS method: DivRes

Energy Days 2018 | INATECH

IBURG

N N N



Intermediate Result: Energy Scenarios



- Two classifications: 80%-90% and 90% CO2 emission reduction target
- Share of electricity generation from wind offshore, wind onshore, PV (average from the scenarios):
 - Reference year: 61% wind onshore, 7% wind offshore, 32% PV
 - Moderate amb: 54% wind onshore, 23% wind offshore, 23% PV
 - Very ambitious: 48% wind onshore, 29% wind offshore, 23% PV

04.08.2021

Energy Days 2018 | INATECH

IBURG

N N N INATECH

¹ Intermediate Result: Energy Scenarios



- Personal vehicle: electric vehicles will dominate mobility sector in 2050
- Moderate amb: electric vehicles, hybrid with biofuels, fuel cell vehicles, natural gas engines
- Very ambitious: electric vehicles, hybrid with synthetic fuels, fuel cell vehicles, no natural gas and fuel based on mineral oil

Energy Days 2018 | INATECH

IBURG

N N N



^H Intermediate Results: Sustainability Indicator

- Three sustainability indicators sets were decided to be defined:
 - Elaborate: all indicators those could be calculated from the models
 - MCDA Input
 - Input for focus groups



(www.abnamro.com)

12



INATECH Intermediate Results: MCDA

- Three MCDA methods which have been selected are:
 - AHP (Analytic Hierarchy Process)
 - TOPSIS (Technique of Order Preference by Similarity of Ideal Solution)
 - PROMETHEE (Preference Ranking Organization Methods for Enrichment Evaluation)





NATECH Conclusion

- The main purpose of the InNOSys project is sustainability assessment of energy scenarios
- Energy scenarios for 2050 were compared and analysed
 - For different sectors (electricity, heat, mobility)
 - Classified into two categories (moderate ambitious and very ambitious)
- Several scenarios with varying "technical storylines" will be selected and recreated
- Three sustainability indicators sets (economical, ecological and social indicators) which were decided to be defined are elaborate set, MCDA input set and focus groups input set
- Multi-criteria assessment method which were selected are AHP, TOPSIS, PROMETHEE





Thank You!

BURG

INI

Claudia Sutardhio

claudia.sutardhio@inatech.uni-freiburg.de